

NKB1000/KBD1000/KB1000

NKB1000/KBD1000/KB1000

Network Keyboard & Control Keyboard & Dome keyboard



NKB1000/KBD1000/KB1000

Network Keyboard & Control Keyboard & Dome keyboard

Features :

Keyboard to Control

- High Speed Dome (all models)
- Standalone DVR (KBD1000 & NKB1000 only)
- Network High Speed Dome (NKB1000 only)
- Network Video Server (NKB1000 only)

Connection

- NKB1000: RS485, RS422, USB, RS232 & Network
- KBD1000: RS485, RS422, USB & RS232
- KB1000 : RS485, RS422 & USB

Functions

- Three Dimensional Joystick Control of PTZ Functions
- Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern

Auxiliary Functions

- On-Screen Menu & User Operation Procedure Tips
- Connect to SmartPSS via USB (NKB1000 only)



NKB1000/KBD1000/KB1000

Network Keyboard & Control Keyboard & Dome keyboard

Technical Specification

Model

| Model | NKB1000 | KBD1000 | KB1000 |
|-------|---------|---------|--------|
|-------|---------|---------|--------|

General

| | | | |
|------------------------|---|---------------------|--------------|
| Keyboard Key panel | Electromechanical | | |
| Joystick | 3-axis, vector-solving, with twisting, return to-center head | | |
| Keyboard Connector | RJ-45, RS232, RS485, RS422, USB | RS232, RS485, RS422 | RS485, RS422 |
| Keyboard Communication | Direct Mode, Network Mode | Direct Mode | Direct Mode |
| Direct Mode | Interface: RS232/RS485 DVR Protocol: DH2 Dome Protocol: DH-SD/PELCO-D/PELCO-P/PELCO-D1/PELCO-P, etc | | |
| Network Mode | Interface: RJ45 DVR/Network Dome: IP Address/Port/ Protocol | N/A | N/A |
| Display | LCD, 75.2mmx33.85mm | | |

Environmental

| | |
|-------------------|---|
| Power Supply | Power adapter, input 100V~240V 50Hz/60Hz, output DC12V/1000mA |
| Power Consumption | 5W |

| | |
|---------------------|---|
| Working Temperature | -10C~+55C |
| Working Humidity | 10%~90% |
| Atmosphere Pressure | 86kpa~106kpa |
| Dimension | 330mmx160(140)mmx37.5(21)mm (WxDxH)(height: 100mm including joystick) |
| Weight | 2.5kg (Including package) |