

120W/48V Din Rail Industrial Power Supply (DP120-48)

120W Industrial Power Supply



- Power Input: AC 90~264V
- Support production for short circuit/over current/over voltage
- Wide temperature range: -40°C ~65°C
- 100% full load aging test
- High efficiency, long life time and high reliability
- Meet EMC Standard

Application

- Industrial Control System
- Semiconductor fabrication equipment
- Factory automation
- Electro-mechanical apparatus

: Description

DP120-48 is one economical slim 120W Din rail industrial power supply series, adapting to be installed on TS-35/7.5 or TS-35/15 mounting rails. The body is designed 40mm in width, which allows spacing inside the cabinets. The entire series adopts the full range AC input from 90VAC to 264VAC and conforms to EN61000-3-2, the norm the European Union regulates for harmonic current.

DP120-48 is designed with metal housing that enhances the unit's power dissipation. With working efficiency up to 89%, the entire series can operate at the ambient temperature between -40°C to 65°C under air convection. It is equipped with constant current mode for over load protection, fitting various inductive or capacitive applications. The complete protection functions and relevant certificates for industrial control apparatus make DP120-48 a very competitive power supply solution for industrial applications.

: Technical Specification

Model	DP120-48	
Output	Group of Output	1
	DC Voltage	48V
	Default Output Voltage	48.00-48.2V (Vin: 220VAC / LOAD: 0A)
	Output Rated Current	2.5A
	Output Current Range	0-2.5A
	Output Rated Power	120W
	Total Peak Output Power	Up to 180W(Sustainable time <u>10S</u> /220VAC)
	Peak Output Current	3.5A(Sustainable time <u>10S</u> /220VAC)
	Ripple noise	Peak - Peak $\leq 100\text{mV}$ (Test Method: The terminal shall be in parallel with capacitance of 0.1uF and 47uF, testing at 20MHz)
	Output Regulation Range	46~56V
	Stabilized Voltage Precision	$\pm 1\%$ (@ 90-264Vac input, 100% load)
	Line Regulation	$\pm 0.5\%$ (@ 90-264Vac input, 100% load)
	Load Regulation	$\pm 1\%$ (@ 90-264Vac input, 100% load)
	Temperature Coefficient	$\pm 0.03\%/^{\circ}\text{C}$
	Output Start Time	< 2S @ nominal input (100% load)
Output Hold Time	> 20ms @ 115Vac, > 50 ms @ 230Vac (100% load)	
Voltage Overshoot	$\leq 5\%$	
Input	Input Voltage Range	90~264VAC
	Input Rated Voltage Range	100~240VAC
	Frequency Range	47Hz~63Hz
	Rated Frequency	50/60Hz
	Starting Voltage	90Vac
	Efficiency	> 90.0% @ 115Vac, > 91.0% @ 230Vac
	Input Current	< 2.20A @ 115Vac, < 1.10A @ 230Vac
	Inrush Starting Current	< 35A @ 115Vac & 230Vac
	Power Factor	> 0.99 @ 115Vac, > 0.93 @ 230Vac

Protection	Output	Over power	144~180W Swing machine (Testing method: Increase the output current until enabling the protection. Protection mode:Swing machine, Self-recovery after over-power released.)	
		Over voltage	57~70V Swing machine (Short circuit the Pin1-2 of U8, swing machine. Output recovery to normal after removing the short circuit) Note: Do not use external voltage.	
		Over current	2.7~3.5A Swing machine (Testing method: Increase the output current until enabling the protection. Protection mode:Swing machine, Self-recovery after over-current released.)	
		Short circuit	It achieves the long-term short circuit by connecting a sufficient cross-sectional area copper cable (Length at 15cm±5cm) with power output port. Self-recovery to normal after removing the short circuit.	
Operation Environment	Operation Temperature and Humidity		-40~65°C ; 20%~95%RH	
	Storage Temperature and Humidity		-40~85°C ; 10%~95%RH non-condensing	
	Libration		Frequency range: 10 ~ 500Hz, Acceleration: 2G, Each sweep cycle 10min. Six sweeps along the X, Y, and Z axis	
	Surge		Acceleration: 20G, Duration time: 11mS, Three shocks along X, Y and Z axis	
	Altitude		2000m	
Safety and EMC Standard @25°C	Security Standard		GB4943/EN60950 ■Reference □Certification	
	Dielectric Strength		Input—Output:3KVac/10mA; Input--Case:1.5KVac/10mA; Output---Case:0.5KVDC/10mA Time for each testing is 1min.	
	Grounding Test		Test Condition: 32A/2min; Ground bond: < 0.1 ohms.	
	Leakage Current		Input to GND ≤3.5mA; Input to output ≤0.25mA (Input 264Vac, 63Hz)	
	Insulation Resistance		Input—Output: 10M ohms;	
	EMI	Conducted Interference		EN55022, EN55024, FCC PART 15 CLASS B
		Radiated		EN55022, EN55024, FCC PART 15 CLASS B

	Interference	
	Harmonic current	EN61000-3-2 CLASS D
EMS	Conducted Emission	EN61000-4-6 Level3
	Radiated Emission	EN61000-4-3 Level3 criterion B
	Power Frequency Emission	EN61000-4-8 Level3
	Electrostatic Emission	EN61000-4-2 Level4 criterion B
	EFT	EN61000-4-4 Level4 criterion B
	Surge	EN61000-4-5 Level4 criterion B
	Dip and Interruption	EN61000-4-11