


i-Net Networks Category5e Patch Cord

Unshielded



Shielded



Compliance

Meets ANSI/EIA/TIA 568-B.2
Meets ISO/IEC 2nd edition 11801 class E
Meets CENELEC EN 50173-1

Highlights

Stranded unshielded & shielded twisted pair patch cord
Shielding against EMI, RFI & alien crosstalk
Fast-Ethernet channel solution

Material

Cable conductor:
7 copper wires $\varnothing 0.16$ mm (0.006"), 24 AWG

Cable insulation:
High Density Polyethylene (HDPE)

Diameter of insulated conductor:
 0.98 ± 0.05 mm (0.039" ± 0.002 ")

Number of pairs/wires:
4-Pairs/8 wires

Color of twisted pairs:
blue-white/**blue**, **orange**-white/**orange**, **green**-white/**green**,
brown-white/**brown**

Unshielded/shielded jacket type & diameter:
PVC/LSZH & $\varnothing 5.5 \pm 0.15$ mm/ $\varnothing 5.8 \pm 0.15$ mm

Outdoor jacket diameter/Color:
RoHS PE 6.3 ± 0.15 mm/Black

Shield:
Aluminum foil

Boot material:
Molded with strain relief

Plug contact:
1.27micron (50 μ inches) gold plated over copper alloy

Ordering

PC5EU-M-01-X	i-Net Networks Patch Cord Category5e Unshielded Stranded 24AWG 4-Pair Milky Gray 1 Feet
U	U-Unshielded, S-Shielded
M	M-Milky Gray, B-Blue, G-Green, Y-Yellow, O-Orange, R-Red, W-White,
03	01-1 Ft, 02-2 Ft, 03-3 Ft, 06-6 Ft, 10-10 Ft, 16-16 Ft, 32-32 Ft, 49-49 Ft, 65-65 Ft, 98-98 Ft
X	L-LSZH (Optional)